

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau


## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>5</sup> : <b>H04M 11/00</b>		<b>A1</b>	(11) International Publication Number: <b>WO 95/01697</b>
			(43) International Publication Date: 12 January 1995 (12.01.95)
(21) International Application Number: <b>PCT/US94/07310</b>		(81) Designated States: CA, JP, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 28 June 1994 (28.06.94)		<b>Published</b> <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	
(30) Priority Data: 08/084,899 29 June 1993 (29.06.93) US			
(71) Applicant: PACIFIC COMMUNICATION SCIENCES, INC. [US/US]; 10075 Barnes Canyon Road, San Diego, CA 92121-2723 (US).			
(72) Inventors: PEPONIDES, George, M.; 632 S. Willowspring Drive, Encinitas, CA 92024 (US). WILE, Stacy; 2827 Cazadero Drive, Carlsbad, CA 92009 (US).			
(74) Agents: DONOHUE, John, P., Jr. et al.; Woodcock Washburn Kurtz Mackiewicz & Norris, 46th floor, One Liberty Place, Philadelphia, PA 19103 (US).			

(54) Title: METHOD AND APPARATUS FOR REDUCING POWER CONSUMPTION IN CELLULAR TELEPHONES AND LIKE RECEIVING DEVICES

## (57) Abstract

A method for reducing power consumption in a cellular telephone that receives multiple copies of a message comprises the steps of receiving a copy of a message block having a plurality of data bits (30); generating soft output signals representative of all data bits in the message block (32); computing a block quality metric indicative of the reliability of the message block (36); comparing the block quality metric with a first threshold (38); if the block quality metric bears a predetermined relation to the first threshold, combining the current message block with a previously accepted message block to obtain a combined message block (42); determining the number of erasures in the combined message block (43); comparing the number of erasures with a second threshold (44) and if below the threshold, decoding the combined message block to determine the number of errors (52), comparing the number of errors with a third threshold (54) and if below the third threshold, accepting the combined message block (56); and generating timing signals instructing the receiving device to interrupt reception of further copies of the current message block for a specified time (58).



*FOR THE PURPOSES OF INFORMATION ONLY*

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

WO 95/01697

PCT/US94/07310

**METHOD AND APPARATUS FOR REDUCING POWER CONSUMPTION IN  
CELLULAR TELEPHONES AND LIKE RECEIVING DEVICES**

**FIELD OF THE INVENTION**

The present invention relates generally to radio-  
5 frequency (RF) communications and receivers therefor, and  
more particularly, to cellular, or mobile, radiotelephones  
(referred to hereinbelow as *cellular telephones*). Still  
more particularly, the present invention relates to methods  
and apparatus for reducing standby power consumption in  
10 analog or dual mode cellular telephones employing the AMPS  
communications standard.

**BACKGROUND OF THE INVENTION**

The preferred application of the present  
invention is in association with an analog cellular  
15 telephone, and thus, the cellular telephone field is the  
technological field most pertinent to the preferred  
embodiments of the invention. However, the present  
invention may also be employed in association with a dual  
mode (analog/digital) cellular telephone and like receiving  
20 devices. Accordingly, except as they may be expressly so  
limited, the scope of protection of the claims appearing at  
the end of this specification is not limited to  
applications of the invention involving an analog cellular  
telephone.

25 Figure 1 is a block diagram of a cellular  
telephone. The cellular telephone includes a radio  
transceiver 10, a demodulator 12, an error correction

WO 95/01697

PCT/US94/07310

- 2 -

decoder 16, and a voice decoder 18, which are all coupled to the speaker portion of a handset 20. (Figure 1 also depicts a bidirectional equalizer 14 that is not relevant to the present invention.) The system further comprises, 5 coupled to the microphone portion of the handset 20, a voice encoder 22, error correction encoder 24 and modulator 26.

The cellular telephone operates in the environment of a cellular system. A cellular system 10 typically includes many cell sites and a centrally-located cellular switch, called a *Mobile Telephone Switching Office* (MTSO). Cell sites are usually spaced at distances of one-half to twenty miles and comprise one or more antennas mounted on a triangular platform placed on a tower or atop 15 a tall building. The fundamental idea behind a cellular system is frequency reuse. This concept of frequency reuse is implemented by employing a pattern of overlapping cells, with each cell conceptually viewed as a hexagon. Frequency reuse allows the cellular system to employ a limited number 20 of radio channels to serve many users. For example, a given geographic area may be served by N cells, divided into two clusters. Each cluster would contain N/2 cells. A separate set of channels would be assigned to each cell in a cluster. However, the sets used in one cluster would 25 be reassigned in the other cluster, thus reusing the available spectrum. The signals radiated from a cell in channels assigned to that cell would be powerful enough to provide a usable signal to a mobile cellular telephone within that cell, but preferably not powerful enough to 30 interfere with co-channel signals in distant cells. All cellular telephones within the system would preferably be capable of tuning to any of the channels.

The Federal Communications Commission (FCC) has allocated a 25 MHz spectrum for use by cellular systems. 35 This spectrum is divided into two 12.5 MHz bands, one of which is available to wire line common carriers only and the other of which is available to non-wire line common

WO 95/01697

PCT/US94/07310

- 3 -

carriers only. In any given system, the non-wire line service provider operates within the "A side" of the spectrum and the wire line provider operates within the "B side" of the spectrum. Cellular channels are 30 KHz wide and include control channels and voice channels. Each cell site (or, where a cell site is sectorized, each sector of that cell site) uses only a single control channel. The control channel from a cell site to a mobile unit is called the "forward" control channel and the control channel from the cellular telephone to the cell site is called the "reverse" control channel. Signals are continuously broadcast over a forward control channel by each cell site.

When a cellular telephone is first turned on, it scans all forward control channels, listening for the channel with the strongest signal. The telephone then selects the forward control channel with the strongest signal and listens for system overhead messages that are broadcast periodically, for example, every 0.8 seconds. These overhead messages contain information regarding the access parameters to the cellular system. The overhead messages also contain busy/idle bits that provide information about the current availability of the reverse control channel for that cell. When the reverse control channel becomes free, as indicated by the busy/idle bits, the cellular telephone attempts to register itself with the system by seizing the reverse control channel.

Cellular telephones, while in an idle or standby mode, must constantly monitor a continuous stream of data messages sent by a cell site over a forward control channel. The format of these messages is depicted in Figure 2 and is explained in more detail in the Electronic Industries Association (EIA) 553 Cellular System specification. The cellular telephone uses a dotting sequence, the first segment of the message, to synchronize the cellular telephone hardware to a clock of the data message. A synchronization word (sync) indicates that the data sequence is about to start. Due to the unreliable

WO 95/01697

PCT/US94/07310

- 4 -

nature of a typical terrestrial propagation channel, messages from a cell site are repeated multiple times. Repeat streams A and B include forty-bit words (which are defined in EIA 553), each word being repeated five times in  
5 the message. Each data word is approximately 4.4 msec "long" and an entire message (or frame), including the dotting sequence, sync word, and streams A, B, is approximately 46.3 msec long. The cellular telephone receives both of the data streams A, B but processes only  
10 one of them. The least significant digit of the unit's telephone number determines which one the data streams is processed. If the telephone number is even, stream A is processed; otherwise stream B is processed. However, to receive and process these data streams, the telephone's  
15 receiver must be on and drawing power the entire time, thereby reducing the time the unit can be used.

U.S. Patent No. 5,175,874, December 29, 1992, titled *Radiotelephone Message Processing for Low Power Operation*, discloses a process for reducing power  
20 consumption in a cellular telephone. The disclosed process receives, digitizes (i.e., quantizes to binary form), and stores a first data word. An error code in the data word is then checked to determine whether errors exist in the word. If there are errors, the digital word is corrected.  
25 A second data word is then received, digitized, checked for errors, and, error corrected if necessary. The second digital word is then compared with the first. If the words are not the same, the receiver remains on until at least two words are identical or the entire five-word message is  
30 received, whichever occurs first. If two received words are equal, the message is processed and the receiver is turned off during the remaining portion of the message, until the next synchronization word is received.

Thus, in the process disclosed in the above-cited  
35 patent, a minimum of two message words must be received, converted to binary form, error corrected, and compared to one another to determine whether they are identical. This

WO 95/01697

PCT/US94/07310

- 5 -

process is therefore limited to systems that encode the message data with an error correction code. In addition, it is believed that the disclosed process provides an unacceptably high average number of words received (note  
5 that a minimum of two words must be received) and unacceptably high probabilities of miss and false acceptance.

#### SUMMARY OF THE INVENTION

A primary goal of the present invention is to  
10 provide improved, in terms of performance and applicability to systems which do not employ error correction coding, methods and apparatus for reducing power consumption in a cellular telephone or like receiving device that receives multiple copies of a message. Pursuant to this goal, the  
15 present invention provides methods for reducing power consumption in a receiving device operating in an environment wherein multiple copies of a message block are transmitted for reception by the receiving device. The inventive methods comprise the steps of receiving a copy of  
20 a message block comprising a plurality of data bits; generating unquantized (soft) output signals representative of all bits in the block; computing a block quality metric indicative of the reliability of the block; comparing the block quality metric with a first threshold; and, if the  
25 block quality metric bears a predetermined relation to the first threshold, combining the current block with a previously accepted block to obtain a combined block. Some embodiments of the invention will interrupt processing of further copies of the block if the block quality metric  
30 bears the predefined relation to the first threshold. However, presently preferred embodiments of the invention continue to the steps of determining whether the combined block includes any erasures (e.g., by employing a second threshold) and, if so, the number of erasures; comparing  
35 the number of erasures with a third threshold and continuing to the following step if the number of erasures

WO 95/01697

PCT/US94/07310

- 6 -

is below the third threshold; decoding the combined block to determine whether it includes any errors and, if so, the number of errors; comparing the number of errors with a fourth threshold and, if the number of errors is below the  
5 fourth threshold, accepting the combined block and continuing to the following step; and generating timing signals instructing the receiving device to interrupt reception of further copies of the message block for a specified period of time.

10 In one preferred implementation of the present invention, the unquantized or soft outputs (i.e., the outputs before the decision variable is converted to a binary format) are generated by sampling the received block at sampling points, or decision points, so as to obtain  
15 representations of the individual bits forming the block.

The block quality metric in preferred embodiments is an average value computed on the basis of the unquantized samples. For example, in one preferred embodiment (described below), the block quality metric  
20 comprises the variance of the signal power (VSP) around the decision points. Another embodiment employs the mean squared error (MSE) around decision points as a block quality metric.

Preferred embodiments further comprise the steps  
25 of rejecting the block and returning to the step of generating unquantized outputs if the block quality metric does not bear the predetermined relation to the first threshold. In addition, preferred embodiments further comprise the steps of rejecting the block and returning to  
30 the step of generating unquantized outputs if the number of erasures is not below the third threshold. Moreover, preferred embodiments further comprise the steps of rejecting the block and returning to the step of generating unquantized outputs if the number of errors (after  
35 decoding) is not below the fourth threshold.

In preferred embodiments of the invention, the number of copies of each message block is predetermined



WO 95/01697

PCT/US94/07310

- 7 -

(e.g., five) and the inventive method includes the steps of, after the step of generating unquantized outputs, determining whether the copy received is the last copy and, if so, generating quantized (hard) decision points for the  
5 block, performing a majority vote with the last block and previously received blocks to construct a hard-combined block, and proceeding directly to the step of decoding the hard-combined block.

The present invention may advantageously be  
10 embodied in a cellular telephone for operation in an environment wherein multiple copies of a message block are transmitted. Such an embodiment preferably comprises a radio transceiver; a demodulator; a voice decoder; a voice encoder; a modulator; and control means for controlling the  
15 operation of the telephone so as to minimize its power consumption. The control means comprises means for controlling the telephone in adaptively determining the quality of the reception of each copy of a received word and in receiving only as many copies as needed to result in  
20 reliable operation.

The present invention exploits the fact that, due to the unreliable nature of a typical terrestrial propagation channel, messages from a central station (e.g., a cell site) to multiple receiving units (e.g., cellular  
25 telephones) are repeated multiple times. According to the invention, the receiving unit adaptively determines the quality of reception of each copy of a received word and receives only as many copies as needed to result in reliable unit operation. Under typical worst case channel  
30 conditions, reception of a single copy of each word is usually sufficient. Therefore, significant power savings result when the receiver and its associated circuitry are powered down during periods when reception of further copies of a word is unnecessary.

35 Other features of the invention are described below.

WO 95/01697

PCT/US94/07310

- 8 -

**BRIEF DESCRIPTION OF THE DRAWINGS**

Figure 1 is a block diagram of a cellular telephone.

Figure 2 illustrates the format of a data stream  
5 (one frame) received from a cell site.

Figure 3 is a flowchart of one preferred embodiment of the inventive method for reducing power consumption in a cellular telephone.

**DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS**

10 The present invention may best be described in connection with a method for operating a receiving device such as a cellular telephone of the kind discussed above with reference to Figure 1. Accordingly, a preferred embodiment of the invention is depicted in Figure 3 as a  
15 flowchart representative of software or firmware controlling a cellular telephone. The physical software is not in itself depicted in the drawings.

Referring to Figure 3, the inventive method begins by initiating the processing of a new frame (step  
20 30). This step involves receiving a first copy of a message block. The method then generates unquantized, soft output signals representative of all bits in the block (step 32). The soft outputs are generated by sampling the received block at decision points to obtain representations  
25 of the individual bits composing the block. For example, if the message frame contains 463 bits and the block contains forty bits, there preferably would be forty decision points at which a sample of the signal waveform would be obtained. The unquantized (soft) samples would  
30 be, in essence, numbers representative of the amplitude of the signal waveform at the respective sampling times (decision points). These numbers would typically be positive and negative voltage values ( $\pm V$ , where  $V$  is unquantized).

35 A determination is then made whether this block is the last block, (step 34). If this is not the last

WO 95/01697

PCT/US94/07310

- 9 -

block, the method computes a block quality metric indicative of the reliability of the block (step 36). The block quality metric in presently preferred embodiments comprises the variance of the signal power (VSP) around  
5 decision points of the block. The VSP may be computed by computing, as error values, the differences between respective sample values squared (which represent the power in the sample) and an average power.

For example, the following formula may be  
10 employed to compute the VSP:

$$VSP = \frac{1}{N} \sum_{i=0}^{N-1} (V_i - \bar{V})^2$$

$$\bar{V} = \frac{1}{N} \sum_{i=0}^{N-1} V_i$$

$$V_i = S_i^2$$

In the above formula,  $S_i$  represents the received signal (sample) at the decision points;  $V_i$  represents the received signal power at the decision points;  $S$  represents the value of the ideal decision point; and  $N$  represents the  
15 length of the block in bits ( $N = 40$  in the present example). The ideal decision point  $S$  represents an ideal voltage sample which would be received in the absence of noise (e.g., plus or minus some constant).

It should be noted that the present invention is  
20 by no means restricted to the use of the VSP as a block quality metric. For example, the mean squared error (MSE) could be used instead of the VSP.

The VSP is then compared with a first threshold  $T_1$  (step 38). For example, the first threshold in  
25 presently preferred embodiments is  $3.88 \cdot V^2$ , where  $V$  represents the square of the ideal decision point  $S$ . If the VSP is less than the first threshold, the first block is combined with a previously "accepted" (see below) block to obtain a soft combined block (step 42). If the VSP is  
30 not less than the first threshold, the block is rejected

WO 95/01697

PCT/US94/07310

- 10 -

(step 40) and the process branches to step 46, which is described below.

After the soft combine step, the method determines the number of erasures in the block (step 43),  
5 the number of erasures being another measure of the quality of the received block. The number of erasures is determined by comparing the signal samples  $S_i$  with a second threshold  $T_2$  and declaring an erasure if  $S_i$  is less than  $T_2$ . The number of erasures is then compared with a third  
10 threshold  $T_3$  (step 44). In presently preferred embodiments, the third threshold is 2. If the number of erasures is less than the third threshold, the method decodes the soft-combined block (step 52), e.g., employing a BCH decoder (where "BCH" refers to the Bose-Chaudhuri,  
15 Hocquenghem error correction coding/decoding technique) and proceeds to step 54. If the number of erasures is not less than the third threshold, the method branches to step 46.

At step 54, the number of errors is determined and this number is compared with a fourth threshold (e.g.,  
20 one). The decoded block is accepted (e.g., by storing it in a buffer) if the number of errors is less than or equal to the fourth threshold (step 56). The method then generates sleep/wake-up signals (step 58) and thereafter waits (step 60) until the next frame is received. The  
25 sleep/wake-up signals are timing signals instructing the receiving device to interrupt reception of further copies of the message block until the next frame begins.

At step 46, the method prepares for receiving the next block. This step essentially comprises setting up the  
30 receiver hardware (e.g., timers) to receive the next block.

As mentioned above, the number of copies of each message block is predetermined (e.g., five). The method determines (step 34) whether the copy received is the last copy and, if so, generates hard decision points for the  
35 block, i.e., quantizes the individual samples (step 48). The method then performs a majority vote with the last block and previously received blocks to construct a hard-

WO 95/01697

PCT/US94/07310

- 11 -

combined block (step 50). The generation of a hard-combined block by majority vote is well known.

The present invention is by no means limited to the threshold values specified above in connection with the detailed description of one presently preferred embodiment. In general, threshold values are determined in the following manner. First, performance criteria are established for the specific application being considered. In the present case, the probability of missing a word and the probability of accepting a word falsely are the selected performance criteria. Ideally, both of these should be made as small as possible. Next, the sensitivity of these performance criteria with respect to each individual threshold is established. Thereafter, the first threshold is established on the basis of the performance criteria being close to where they should be. Then the next threshold is established to move the performance criteria closer to their target values. The process is then repeated with the next threshold, and so on, until the expected performance of the system meets the preestablished performance criteria. Finally, although two criteria were employed in the above example, it should be noted that one criterion may be sufficient in particular applications.

Finally, it should be noted that the scope of protection of the following claims is not limited to the particularities described above in connection with the presently preferred embodiments. For example, the invention may be practiced in association with a receiving device other than a cellular telephone.

WO 95/01697

PCT/US94/07310

- 12 -

We claim:

1. A method for reducing power consumption in a receiving device operating in an environment wherein multiple copies of message blocks are transmitted from a transmission device for reception by said receiving device, comprising the steps of:
  - (a) receiving a copy of a current message block comprising a plurality of data bits;
  - (b) generating unquantized output signals representative of all data bits in said current message block;
  - (c) computing, on the basis of said unquantized output signals, a block quality metric indicative of the reliability of said current message block;
  - (d) comparing said block quality metric with a first threshold; and
  - (e) if said block quality metric bears a predetermined relation to said first threshold, generating timing signals instructing said receiving device to interrupt reception of further copies of said current message block for a specified period of time.
2. A method as recited in claim 1, further comprising, before generating said timing signals, the steps of:
  - (f) combining said current message block with a message block previously accepted by said receiving device to obtain a combined message block;
  - (g) determining whether said combined message block includes any erasures and, if so, the number of erasures, wherein the number of erasures is determined by comparing samples of said combined message block with a second threshold and declaring an erasure if a sample is less than said second threshold;
  - (h) comparing said number of erasures with a third threshold;

WO 95/01697

PCT/US94/07310

- 13 -

(i) if the number of erasures is below said third threshold, decoding the combined message block to determine whether it includes any errors and, if so, the number of errors; and

- 5 (j) comparing said number of errors with a fourth threshold and, if the number of errors is below said fourth threshold, accepting said current message block.

3. A method as recited in claim 1, wherein said step of computing the block quality metric comprises the  
10 step of determining the variance of the signal power (VSP) around decision points of the current message block.

4. A method as recited in claim 1, wherein said step of computing the block quality metric comprises the step of determining the mean squared error (MSE) around  
15 decision points of the current message block.

5. A method as recited in claim 1, further comprising the steps of rejecting said current message block and returning to step (b) if, at step (d), said block quality metric does not bear said predetermined relation to  
20 said first threshold.

6. A method as recited in claim 2, further comprising the steps of rejecting said current message block and returning to step (b) if, at step (h), said number of erasures is not below said third threshold.

25 7. A method as recited in claim 2, further comprising the steps of rejecting said current message block and returning to step (b) if, at step (j), said number of errors is not below said fourth threshold.

8. A method as recited in claim 2, wherein the  
30 number of copies of each message block is predetermined and further comprising the steps of, after step (b),

WO 95/01697

PCT/US94/07310

- 14 -

determining whether said copy of the current message block received at step (a) is the last copy of the current message block and, if so, generating quantized decision points for said current message block, performing a majority vote with said last copy of the current message block and message blocks previously accepted by said receiving device to construct a hard-combined message block, and proceeding directly to step (i) to decode said hard-combined message block.

9. A receiving apparatus for operation in an environment wherein multiple copies of message blocks are transmitted by a transmitting apparatus for reception by said receiving apparatus, comprising:
- (a) means for receiving a copy of a current message block comprising a plurality of data bits;
  - (b) means for generating unquantized output signals representative of all data bits in said current message block;
  - (c) means for computing, on the basis of said unquantized output signals, a block quality metric indicative of the reliability of said current message block;
  - (d) means for comparing said block quality metric with a first threshold;
  - (e) means for combining said current message block with a message block previously accepted by said receiving means to obtain a combined message block if said block quality metric bears a predetermined relation to said first threshold;
  - (f) means for decoding said combined message block; and
  - (g) means for interrupting reception of further copies of said current message block for a specified period of time.



WO 95/01697

PCT/US94/07310

- 15 -

10. An apparatus as recited in claim 9, wherein said computing means computes the variance of the signal power (VSP) around decision points of the current message block.

5 11. An apparatus as recited in claim 9, wherein said computing means computes the mean squared error (MSE) around decision points of the current message block.

12. An apparatus as recited in claim 9, further comprising means for rejecting said current message block  
10 if said block quality metric does not bear said predetermined relation to said first threshold.

13. An apparatus as recited in claim 9, further comprising means for determining the number of erasures in said combined message block and rejecting said current  
15 message block if said number of erasures is not below a second threshold.

14. An apparatus as recited in claim 13, further comprising means for determining the number of errors in said combined message block and rejecting said current  
20 message block if said number of errors is not below a third threshold.

15. An apparatus as recited in claim 9, wherein the number of copies of each message block is predetermined and further comprising means for determining whether the  
25 copy of the current message block being processed is the last copy of the current message block and, if so, generating quantized decision points for said current message block, performing a majority vote with said last copy of the current message block and message blocks  
30 previously accepted by said receiving means to construct a hard-combined message block.

WO 95/01697

PCT/US94/07310

- 16 -

16. A cellular telephone for operation in an environment wherein multiple copies of a message block are transmitted by a transmitting device, comprising a radio transceiver; a demodulator; a voice decoder; a voice  
5 encoder; a modulator; and control means for controlling the operation of the telephone so as to minimize its power consumption, said control means comprising means for controlling the telephone by adaptively determining the reliability of the reception of each copy of a received  
10 message block and, if a current copy of said received message block has a suitable signal quality, ignoring subsequent copies of said received message block for a predetermined period of time.

17. A cellular telephone as recited in claim 16,  
15 wherein said control means comprises:

- (a) means for receiving a copy of a current message block comprising a plurality of data bits;
- (b) means for generating unquantized output signals representative of all data bits in said current  
20 message block;
- (c) means for computing, on the basis of said unquantized output signals, a block quality metric indicative of the reliability of said current message block;
- 25 (d) means for comparing said block quality metric with a first threshold;
- (e) means for combining said current message block with a message block previously accepted by said receiving means to obtain a combined message block if said  
30 block quality metric bears a predetermined relation to said first threshold;
- (f) means for determining whether said combined message block includes any erasures and, if so, the number of erasures;
- 35 (g) means for comparing said number of erasures with a second threshold;

WO 95/01697

PCT/US94/07310

- 17 -

(h) means for decoding the combined message block to determine whether it includes any errors and, if so, the number of errors;

(i) means for comparing said number of errors  
5 with a third threshold and, if the number of errors is below said third threshold, accepting said current message block; and

(j) means for interrupting reception of further  
copies of said current message block for a specified period  
10 of time.

WO 95/01697

PCT/US94/07310

1 / 2




FIG. 1




FIG. 2

WO 95/01697

2 / 2 ,

PCT/US94/07310




FIG. 3

## INTERNATIONAL SEARCH REPORT

 International application No.  
PCT/US94/07310

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(5) : H04M 11/00

US CL : 379/59

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 379/59, 58, 63, 356, 355, 67, 88

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	JP, A, 62-23266 (NUMATA et al.) 31 January 1987, Figure 1 and text describing the figure.	1-21
A	US,A, 4,885,762 (SUZUKI, et al.) 05 December 1989	1-21
A	US,A 4,852,146 (HATHCOCK et al.) 25 July 1989	1-21
A	US,A 5,212,721 (DELUCA et al.) 18 May 1993	1-21
A	US,A 4,117,542 (KLAUSNER et al.) 26 September 1978	1-21

☐ Further documents are listed in the continuation of Box C.
 ☐ See patent family annex.

* Special categories of cited documents:	
*A* document defining the general state of the art which is not considered to be part of particular relevance	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*E* earlier document published on or after the international filing date	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*O* document referring to an oral disclosure, use, exhibition or other means	
*P* document published prior to the international filing date but later than the priority date claimed	*A* document of the same patent family

Date of the actual completion of the international search

27 SEPTEMBER 1994

Date of mailing of the international search report

22 NOV 1994

 Name and mailing address of the ISA/US  
 Commissioner of Patents and Trademarks  
 Box PCT  
 Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

MARK KELLY

Telephone No. (703) 305-4700